

HYDRO
ENGINEERING

40' FRONT FOLD TOOLBAR

LASTING | INNOVATIVE | IMPERVIOUS
EST. 1971



QUALITY SYSTEMS, QUALITY SOLUTIONS



Design

Folded dimensions of bar optimized for transport -
35,600lbs, 14'5" W, 30'6" L, 11'6" H

Features

- Anti-lean turn force system to increase bar stability during turns
- Power-assist swing tube
- ISOBUS compatible
- Superior tire floatation
- Protected 8" flow meter
- Easy to switch to another tractor if one breaks down
- Places load on the hitch to protect your tractor's rear axles

Patent Pending

Operation

- Best-in-class visibility with the industry's leading low profile swing tube and all around lighting package
- Reach your target injection zone with 4-12" adjustable tillage depth
- Requires 425-450 drawbar horsepower minimum



Injectors

Utilizes DSI Python injectors with 30° pivoting capabilities to each side on 24" spacings with other tillage options available

HYDRO
ENGINEERING

952-467-3100 | sales@hydro-eng.com

www.hydro-eng.com

301 Industrial Blvd, Norwood Young
America, MN 55397

2026 Hydro Engineering. Hydro Engineering, may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional. The information contained in this brochure is intended to be of a general nature only, specific operations may vary from the average, and both crop and machine management, as well as the weather, are important factors in the end result. Attention: Photographs in this publication may show protective shields or guards open or removed for the purposes of illustration. Be certain all shields and guards are properly in place during operation. Printed in the U.S.A.