HYDRO ENGINEERING

# GK150-75

LASTING | INNOVATIVE | IMPERVIOUS
EST. 1971

MUNICIPALITIES

# Quality Systems, Quality Solutions

## Mobility, Power, & Reliability

Enclosure allows sound-level compliance* for use in residential areas.
**Target sound level: <75 dB at 30' distance*

The maximum flow rate of 2,750 GPM is powered by our combination of:

- 2.8L 75HP Cummins Engine
- Cornell 6NNT Redi-Prime Pump

This pump station can come with or without the sound attenuation enclosure.

**Features:**

- 6" Suction and Discharge
- Pump unit can be disconnected from trailer for versatile placement
- Can be set-up and used by single operator
- Easy service access both with and without sound enclosure
- Integrated sliding skid enables quick pump service or removal

HYDRO ENGINEERING

**952-467-3100** | **sales@hydro-eng.com**

www.hydro-eng.com

301 Industrial Blvd, Norwood Young America, MN 55397

2023 Hydro Engineering. Hydro Engineering, may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional. The information contained in this brochure is intended to be of a general nature only, specific operations may vary from the average, and both crop and machine management, as well as the weather, are important factors in the end result. Attention: Photographs in this publication may show protective shields or guards open or removed for the purposes of illustration. Be certain all shields and guards are in place during operation. Printed in the U.S.A.